

EST Group, a business unit of Curtiss-Wright Flow Control Company

2701 Township Line Road, Hatfield, PA 19440

Telephone: (215) 721-1100 800-355-7044 Fax: (215) 721-1101

E-Mail: est-info@curtisswright.com Website: estgroup.cwfc.com

GripTight® High Pressure Test Plug



I.D. sealing test plug for high pressure hydrostatic testing of pipe, pipelines and pressure vessels.

Note: Never use a test pressure greater than the weakest component in the system can handle. Test Pressure specified in table is equivalent to 80% of the pressure that will yield ASTM A106 Grade B pipe. The test pressure for higher and lower strength pipes will differ proportionally. The maximum test pressure for higher strength pipe must never exceed the highest test pressure listed for that pipe O.D.

Specifications subject to change without notice.

Results 51 - 75 of 153

Item #	Nominal Pipe Size (in)	Nominal Pipe Schedule	Pipe I.D. Size Range (in)	Pipe I.D. Size Range (mm)	Plug O.D. (in)	Plug O.D. (mm)	Maximum Test Pressure (psi)	List Price
GT-5P160	5	160	4.28 to 4.47	108.7 to 113.5	4.17	105.9	7,000	QUOTE
GT-442T	-	-	4.42 to 4.58	112.3 to 116.3	4.31	109.5	See Pressure Note	QUOTE
GT-5P120	5	120	4.53 to 4.69	115.1 to 119.1	4.42	112.3	5,500	QUOTE
GT-466T	-	-	4.66 to 4.82	118.4 to 122.4	4.55	115.6	See Pressure Note	QUOTE
GT-5P80	5	80	4.78 to 4.91	121.4 to 124.7	4.67	118.6	4,000	QUOTE
GT-6PXXS	6	XXS	4.87 to 5.11	123.7 to 129.8	4.76	120.9	8,200	QUOTE
GT-5P40	5	40	5.02 to 5.14	127.5 to 130.6	4.91	124.7	2,700	QUOTE
GT-514T	-	-	5.14 to 5.26	130.6 to 133.6	5.03	127.8	See Pressure Note	QUOTE
GT-6P160	6	160	5.16 to 5.37	131.1 to 136.4	5.05	128.3	6,700	QUOTE
GT-5P10	5	10	5.27 to 5.39	133.9 to 136.9	5.16	131.1	1,400	QUOTE
GT-5P5	5	5	5.32 to 5.44	135.1 to 138.2	5.21	132.3	1,100	QUOTE
GT-534T	-	-	5.34 to 5.51	135.6 to 140	5.23	132.8	See Pressure Note	QUOTE
GT-6P120	6	120	5.47 to 5.64	138.9 to 143.3	5.36	136.1	5,100	QUOTE
GT-562T	-	-	5.62 to 5.76	142.7 to 146.3	5.51	140	See Pressure Note	QUOTE
GT-6P80	6	80	5.73 to 5.87	145.5 to 149.1	5.62	142.7	3,900	QUOTE
GT-588T	-	-	5.88 to 6.03	149.4 to 153.2	5.76	146.3	See Pressure Note	QUOTE
GT-6P40	6	40	6.04 to 6.17	153.4 to 156.7	5.92	150.4	2,500	QUOTE
GT-618T	-	-	6.18 to 6.32	157 to 160.5	6.06	153.9	See Pressure Note	QUOTE
GT-6P10	6	10	6.33 to 6.47	160.8 to 164.3	6.21	157.7	1,200	QUOTE
GT-6P5	6	5	6.38 to 6.52	162.1 to 165.6	6.26	159	940	QUOTE
GT-653T	-	-	6.53 to 6.67	165.9 to 169.4	6.41	162.8	See Pressure Note	QUOTE
GT-668T	-	-	6.68 to 6.82	169.7 to 173.2	6.56	166.6	See Pressure Note	QUOTE
GT-8P160	8	160	6.78 to 7.04	172.2 to 178.8	6.66	169.2	6,400	QUOTE
GT-8PXXS	8	XXS	6.85 to 7.09	174 to 180.1	6.73	170.9	6,200	QUOTE
GT-8P140	8	140	6.97 to 7.2	177 to 182.9	6.85	174	5,700	QUOTE

Results 51 - 75 of 153